

The SLIT HS COMPACT series slitter is ideal for all types of flexible packaging materials as well as label stock. The compact design with integrated unwind allows for easy install and space allocation. The machine comes with both razor & shear knifes, both adjustable from operator side. This machine is ideal for budget conscious flexible packaging converter looking for compact design.

Machine Specifications

Description	Spec
Speed	400 m/min
Web Width	800 / 1000 / 1300 mm max
Unwind Roll Diameter	800 mm
Unwind Roll Weight	1.200kg max
Unwind Roll Cores	3" I.D 6" I.D. (option)
Finished Roll Diameter	3" I.D 6" I.D. (option)
Slit Width	50 mm and up (Lower Upon Request)
Knifes	Shear & Razor
Winding Tension	0.5 pli to 2.5 pli (11 - 45 kg) standard

Vacuum Hug Drum

Benefits

- Absolute Tension Isolation between Unwind and Rewind
- Slip Free Web Transport
- Avoids Wrinkles

Main Drive Higher Efficiency vs. Nip Design Allows maximum Machine Speed while maintaining precise tension control



Slice and Inspection Table

Ideal for Additional Doctoring Capacity The slitting process is accomplished at higher precision Strobe Light Sync to Speed Three Types of Inspection Tables:

- Inspection Table with Splice Table
- Splice Table Only
- Inspection Table Only



Layout

