

Steamtec



**KARLVILLE**

High Performance Steam Tunnel.

## Machine Specifications

Description	Spec
Speed	Until 250 BPM
Available Lengths	2000 / 3000 mm
Max Sleeve Height	380 mm
Max Container Height	400 mm
Max Container Diameter	170 mm

### SteamPro - Standard Market Solution

- Up / Down – Adjustable
- In / Out – Adjustable to Match Bottle Shape
- Pipe Angle – Adjustable
- Nozzle Rotation – Adjustable

### SteamPro - Standard Market Solution

- 100-350 Kg/Hr Depending on Length and Application

To learn more about our products visit: [www.karlvile.com](http://www.karlvile.com)

US: +1-305-533-1051 | Europe: +33-472-81-2929

## Information

### Flow control

- Pressure regulation inlet & outlet
- Individual raw valve flow control
- Smart Karlville boiler regulation control
- Low power requirement thanks to optimal design

### Ramp setting

- 1,2m long ramps
- Flow control operated from one side
- Up/Down adjustment
- Neck focus thanks to angular adjustment
- Micro holes for smooth and homogenate fog

### Design

- Dual chamber for energy saving with glass windows and width adjustment for energy saving
- Super heater
- Integrated boiler
- Water pre heated pipeline
- Flow and pressure smart control
- No net work insulation requirement
- Integrated electrical cabinet

## Layout

